



三段式自動化電腦玻璃切割機

AUTO LOADING&CUTTING&BREAKING GLASS CUTTING MACHINE



簡單的圖庫操作

Graphs stock easy to sperate.

(A) 基本圖形 (鏡業·傢俱業使用) :


BASIC GRAPHS



仿形輸入

(b) 變形+直線切割 :

SHAPE + STRAIGHT CUTTING



(C) 直線排版切割

STRAIGHT-CUTTING COMBINATION



特點 :

專為深加工玻璃設計採用電腦控制器，伺服馬達與精密齒排，機台本身裝配輸送皮帶降低玻璃刮傷，輸入可選擇中英文對話方式輸入操作簡易，方便修改尺寸，另可選配自動排版軟體+數位板，切割準確，提高品質及產能，以節省人工及維護現場安全，適合傢俱及建材玻璃等使用。

提供辦公室作業系統 :

1. 電腦+ATOCAD轉換DXF軟體 (附圖庫)
2. 自動排版優化軟體
3. 仿形軟體+數位板12"×12"-60*48"(選購)

規格 :

- 切割厚度：2MM-12MM/3MM-19MM
- 切割精度：(直線)+/-0.20MM (異形)+/-0.25MM
- 切割速度：0-100M/MIN
- 輔助系統：氣壓一彈簧並用
- 自動供油裝置的切割油大都集中在切線上
- 切割台上附有輸送皮帶3-5條，當切割完成時送出玻璃減少刮傷
- 控制系統：CNC控制器+電腦系統
- 程式傳輸方式：RS-232
- 傳動系統：採用X-Y-C伺服馬達與精密齒排
- 電壓：S3 220V/380V/415V 50/60HZ 50A
- 空壓：5KG/CM² 風壓接頭：PT1/4"

FEATURE:

THE MACHINE IS ADOPTED CNC-CONTROLLER WITH P.C., SERVO MOTOR AND PRECISION RACK ETC.DEVICE SPECIAL SUITABLE FOR CUTTING GLASS SHAPE AND STRAIGHT PROFILE. THE SURFACE OF THE MACHINE IS EAUIPPED WITH THE BELT CONVEYOR SYSTEM TO FACILITATE GLASS DELIVERY EASY TO OPERATE AND CUTTING PRDCISION AND INCREASE THE WORKING EFFICIENCY AND QUALITY AND SAFETY.

SUITABLE FOR:

FURNITURE, BUILDINGS, DELIVERY AUTOMOBILE MIRROR, LIGHT, GIFT, MIRROR, ETC.

SPECIFICATION:

- THICKNESS OF CUTTING: 2MM-12MM/3MM-19MM
- PRECISION OF CUTTING: STRAIGHT: +/-0.20MM SHAPE: +/-0.25MM
- SPEED OF CUTTING: 0-100M/MIN.
- AUXILIARY SYSTEM: AIR COMPRESS & SPRING COMBINATION
- THE OIL FORM LUBRICANT SYSTM MOSTLY CONCENTRATED ON THE LINE OF CUTTING.
- THE SURFACE OF THE MACHINE IS EQUIPPED WITH THE BELT MOTOR SYSTEM TO FACILITATE GLASS DELIVERY WHEN CUTTING FINISHING.
- CONTORLLER SYSTEM: CNC CONTROLLER WITH P.C.
- PROGRAM TRANSFER: RS-232
- DELIVERY SYSTEM: ADOPTED X-Y-C SERVO MOTOR AND PRECISION RACK
- AIR COMPRESS: 5KG/CM² PT1/8"
- VOLTAGE: S3 220V/380V/415V 50/60HZ 50A



CUTTING SECTION:切割機 (B):

機型	最大玻璃尺寸長×寬	最小玻璃尺寸長×寬	機台尺寸/重量
MODEL	MAX. GLASS SIZE LEIGHT-WIDTH	MIN. GLASS SIZE LEIGHT-WIDTH	TOTAL LENGTH-WIDTH-HEIGHT
CNC F-9672	2440 MM × 1830 MM (96" × 72")	1520 M M × 122 0M M (60" × 48")	3200MM × 2600M M × 1450M M
CNC F-144108	3660 MM × 2750 MM (144" × 108")	2000 M M × 155 0M M (80" × 60")	4500MM × 3800M M × 1450M M

LOADING SECTION:送料機 (A):

機型	最大玻璃尺寸長×寬	最小玻璃尺寸長×寬	機台尺寸/重量
MODEL	MAX. GLASS SIZE LEIGHT-WIDTH	MIN. GLASS SIZE LEIGHT-WIDTH	TOTAL LENGTH-WIDTH-H EIGHT
FD-9672	2440 MM × 1830 MM (96" × 72")	1520 M M × 122 0M M (60" × 48")	3200MM × 2600M M × 850M M
FD-144108	3660 MM × 2750 MM (144" × 108")	2000 M M × 155 0M M (80" × 60")	4500MM × 3800M M × 850M M

+ Vacuum Frame: Single Side Or Double Side

+ Delivery Sheet Way: The loader is equipped with the rubber rolling to facilitate glass delivery

BREAKING SECTION:升桿剝台(C)

機型	最大玻璃尺寸長×寬	機台尺寸/重量	剝片棒
MODEL	MAX. GLASS SIZE LEIGHT-WIDTH	TOTAL LENGTH-WIDTH-HEIGHT	AUXILIARY SYSTEM BREAKING BAR
CH-9672	2440MM × 1830(96" × 72")	2750M M × 215 0M M × 850M M	NO
BH-144108	3660MM × 2750(144" × 108")	4000M M × 290 0M M × 850M M	2

+ Delivey Sheet System: The surface of the machine is equipped with air blower to facilitate glass delivery when breaking glass.